

# AN5261

## Optical Network Unit

### Datasheet

#### Overview

The AN5261 is a CBU ONU independently developed by FiberHome, supporting both GPON and XGS-PON upstream transmission. Used together with OLT equipment at a central office, it provides services such as Ethernet access and clock synchronization signal transmission for small-sized base station subscribers.

The AN5261 can be flexibly deployed. It can be placed on a plane, secured on a wall, or mounted in a cabinet to adapt to various scenarios.

#### Highlights

- Multiple mounting modes, easy installation, and flexible deployment
- Multiple time and clock synchronization modes; good adaptability to various network environments
- Type B and Type C protection switching with high reliability
- High-class lightning protection design for stable operation

## Appearance and Specifications

### AN5261



| Classification                  | Item                      | Specification  |
|---------------------------------|---------------------------|--|
| Mechanical parameters           | Dimensions (H × W × D)    | 44 mm × 440 mm × 225 mm  |
|                                 | Weight                    | 2.4 kg   |
| Power supply parameters         | Voltage                   | -48 V DC   |
|                                 | Current                   | ≤ 1 A  |
| Power consumption parameters    | Static power consumption  | 15 W   |
|                                 | Maximum power consumption | 32 W   |
| Environment parameters          | Operating temperature     | -30°C to 55°C  |
|                                 | Storage temperature       | -40°C to 70°C  |
|                                 | Ambient humidity          | 5% to 95% (no condensation)  |
| Lightning protection parameters |                           | <ul style="list-style-type: none"> <li>Lightning protection for power supply and service ports, complaint with the EMC standard ITU-T K.21</li> <li>Power supply: 6 kV in both common and differential modes</li> <li>GE ports: 4 kV in common mode; 0.5 kV in differential mode</li> </ul>                      |
| Mounting modes                  |                           | Plane mounting, wall mounting and cabinet mounting   |
| Network side interfaces         | Interface configuration   | 2 × GPON ports or 2 × XGS-PON ports  |
|                                 | Port type                 | SC/UPC <ul style="list-style-type: none"> <li>GPON: SFP</li> <li>XGS-PON: SFP+</li> </ul>  |
|                                 | Port rate                 | <ul style="list-style-type: none"> <li>GPON: 1.25 Gbit/s (upstream) / 2.5 Gbit/s (downstream)</li> <li>XGS-PON: 9.953 Gbit/s (both upstream and downstream)</li> </ul>   |
|                                 | Standard compliance       | <ul style="list-style-type: none"> <li>GPON: ITU-T G.984</li> <li>XGS-PON: ITU-T G.9807.1</li> </ul>   |
|                                 | Interface functions       | <ul style="list-style-type: none"> <li>Pluggable optical modules</li> <li>Type B and Type C protections</li> </ul>   |
| User side interfaces            | Interface configuration   | 4 × GE ports, 2 × GE optical ports, 1 × 10GE optical port, 1 × 1PPS+TOD port   |
|                                 | Port type                 | <ul style="list-style-type: none"> <li>GE / 1PPS+TOD ports: RJ-45</li> <li>GE optical ports: SFP</li> <li>10GE optical port: SFP+</li> </ul>   |
|                                 | Port rate                 | <ul style="list-style-type: none"> <li>GE ports: auto-negotiated to rates 10 / 100 / 1000 Mbit/s</li> <li>GE optical ports: 1 Gbit/s</li> <li>10GE optical ports: 10 Gbit/s</li> </ul>   |
|                                 | Standard compliance       | IEEE 802.3   |
|                                 | Interface functions       | <ul style="list-style-type: none"> <li>Configuration of Ethernet port rate, working mode, port enabling, and auto-negotiation mode</li> <li>Loop detection on Ethernet ports</li> <li>In-band IEEE 1588v2 functions and synchronous Ethernet</li> <li>BITS and 1PPS+TOD clock synchronization signals</li> </ul> |

## Functions and Features

### Multicast

- IGMP v2/v3
- IGMP Snooping
- MLD

### Clock Synchronization

- In-band IEEE 1588v2 functions
- Synchronous Ethernet
- BITS and 1PPS+TOD clock synchronization

### QoS and ACL

- ACL: traffic matching based on ACL rules
- QoS: service flow priority queues and scheduling of them
- Traffic rate control and priority remarking based on traffic classification rules
- Rate control on Ethernet ports
- Flow control based on PAUSE frames
- Traffic management based on DBA and priority to meet subscribers' demand for minimum designated bandwidth and low latency for high-priority services

### Layer 2 Management

- Line identifiers
- MAC address management
- Transparent transmission of BPDUs
- IEEE 802.1p and 802.1Q
- VLAN stacking
- Transparent transmission and 1:1 translation of VLAN tags
- Multicast packets carrying VLAN tags
- Adding / stripping of VLAN tags based on Ethernet ports

### Security

- Limit on number of MAC addresses per port
- Broadcast storm suppression on user ports and uplink ports
- Protection against various network attacks (including ARP attack, ICMP attack, DOS attack, and BPDU attack)
- MAC / IP address filtering

### OAM

- Equipment management via a Web-based network management system: Allows login to the equipment via a user LAN port to view equipment information and modify settings such as the ONU's logical SN and password.
- Remote management in Telnet mode: Displays ONU status and prints debugging information.
- OMCI protocol
- DHCP line identifiers
- PPPoE+

